DOLPHIN





DB200 / DB225

DOLPHIN ELECTRONIC INFRARED TAP

› Touch Free Tap – for ultimate hygiene – prevents cross contamination
› Special Finishes: PPC in all RAL colours, Mirror Polished or 316 Stainless Steel
› Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications. 3/8" BSP water supply connector
› Flow time once user's hands are removed from the tap - 1 second (adjustable by using remove control DB51)
› Hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on
› 2 year manufacturer's warranty
› Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
› WRAS approved, also complies with SKA rating criteria
› Fully BREEAM compliant and contributes to up to five BREEAM WAT1 credits.
› Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits
› Power Source: 9 Volt Battery / Plug-in 9 Volt transformer. Power connections: tap: male / power source: female
› Counter Hole: diameter 28-34mm. Minimum/maximum counter thickness: 2-27mm

HEIGHT	**142MM**
DIAMETER	**50MM**
PROJECTION	**60MM**

PRODUCT CODES

DB200C - Battery, polished finish
DB225C - Transformer, polished finish
DB200.5 - Battery, powder coating finish
DB225.5 - Transformer, powder coating finish
DB200.6 - Battery, ceramic coating finish
DB225.6 - Transformer, ceramic coating finish
DB200-316 - Battery, 316 stainless steel
DB225-316 - Transformer, 316 stainless steel

TECHNICAL HELPLINE 01424 202224
DOLPHINSOLUTIONS.COM