





DS213

DOLPHIN SLIMLINE INFRARED BASIN TAP

- > Dolphin Up and Over Thru Counter Mounted Inform Tap
- > Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel
- > Self-monitoring analysis and recording technology (smart) allows the Facilities Manager to connect point to point via the Dolphin Inform App when used with the optional Bluetooth Adaptor (Sold separately Order product code 25148)
- > Infrared Touch Free Tap for ultimate hygiene prevents cross contamination sensor mounted in end of 55° spout
- > Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 4, 3, 2, 1.75
- \rightarrow Water supply: single inlet cold or pre-mixed a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Maximum operating water temperature 60°C
- > Nominal current: Less than ImA (Less then 25mA with Bluetooth)
- > Nominal power: Less than IW
- > Security time can be adjusted via the App default 20 seconds (60 seconds max)
- > IP68 connector
- > Power Source: Plug-in 9 Volt transformers, hard wired transformers, or battery packs
- > Recommended minimum distance between sensor and the bottom of basin = 200mm
- > WRAS approved
- > Comes with laminar flow feature to avoid splashing
- > Comes as standard with 24 hour line purge/hygiene flush feature, with alterable timings

HEIGHT I50/200MM PROJECTION I50/200MM DIAMETER 22MM



