


DB400 / DB425

DOLPHIN PANEL MOUNTED ELECTRONIC INFRARED TAP

- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished chrome plated brass or brushed satin stainless steel finishes available from stock – other finishes available to special order
- › Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
- › Flow time once user's hands are removed from the tap - 1 second (adjustable by using remote control DB5 I)
- › Interchangeable STD M22/24 Neoperl Aerator insert
- › Tap settings may be adjusted by using remote control (DB5 I)
- › Power Source: 6 x AA Battery / plug in 9v Transformer. Power Connections: tap female, power source male
- › Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- › Maximum water temperature 70°C
- › To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB5 I). Taps are supplied with this feature switched on
- › 2 year manufacturer's warranty
- › WRAS approved, and complies with SKA rating criteria
- › To special order we can supply a threaded tail extension kit
- › Fully BREEAM compliant and contributes to up to five BREEAM WAT 1 credits.
- › Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. This allows businesses purchasing these product to benefit from 100% first year capital allowances on this expenditure

DIAMETER	38MM
PROJECTION	170MM

PRODUCT CODES

DB400C - Battery powered, polished finish

DB400-316 - Battery powered, satin finish

DB425C - Transformer powered, polished finish

DB425-316 - Transformer powered, satin finish



SKArating®