DOLPHIN



DS241

DOLPHIN INFORM 90 DEGREE SWAN NECK TAP

› Dolphin Counter Mounted InForm (SMART) 90 degree Swan neck Tap
› Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel.
› Self-Monitoring Analysis and Recording Technology (SMART) allows the Facilities Manager to connect point to point via the Dolphin SMART App when used with the optional Bluetooth Adaptor (Sold separately -Order product code 25148)
› Infra-Red Touch FreeTap for ultimate hygiene prevents cross contamination
› Sensor mounted in the spout of the tap, not in the body or external
› Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25 and 1.75LPM flow rates on special request
› Water Supply: Single inlet cold or pre-mixed aTMV2 orTMV3 thermostatic mixing valve is recommended for premixed applications
› Maximum operating water temperature - 60°C
› Nominal Current: Less than 1mA (Less than 25mA with Bluetooth)
› Nominal Power: Less than 1W
› Security Time can be adjusted via the App Default 20 Seconds (60 Seconds max)
› IP68 Connector
› Manufactured in the UK
› Available with a laminar flow option instead of standard aerator
› KUKreg4 approved

DIAMETER	**22MM**
HEIGHT	**275MM**
PROJECTION	**150/200MM**

PRODUCT CODES

DS241.150.275 - 90 degree Swan Neck Smart Tap, 150mm projection, 275mm height
DS241.200.275 - 90 degree Swan Neck Smart Tap, 200mm projection, 275mm height
DS243.150.275 - 55 degree Swan Neck Smart Tap, 200mm projection, 275mm height
DS243.200.275 - 55 degree Swan Neck Smart Tap, 200mm projection, 275mm height

TECHNICAL HELPLINE 01424 202224
DOLPHINSOLUTIONS.COM