DOLPHIN



DC3090.1

FLOOR MOUNTED ULTRAFLUSH WC SET – MECHANIC

DETAILS

› **Full set with all items included for a working WC**

› **Declarations of performance and conformity**

› **Dual flush volumes of 6/3 litres as standard, adjustable to 4.5/3**

› **Special Finishes: Satin Brushed Stainless Steel, Ceramic Coating, PPC in all RAL colours**

› The UltraFlush system reduces noise while efficiently circulating water around the pan, ensuring perfect cleaning and a more comfortable user experience

› Mechanical actuation flush

› Pan & cistern weight tested to 400KG

› WRAS approved inlet valve

› Compliant with DEFRA Interim agreement

› EN14055 Class two compliant

› Working pressure: 0.1 to 16 bar

› Actuation force <20N

› Opening in the final wall finish should be cut to the size of the flush plate, not to the size of the cistern opening

› Minimum wall thickness is 15mm

SET INCLUDES

› DC2014 UltraFlush WC pan and seat

› DB5510.M Cistern (frameless)

› DB5560.M Flush plate

FLUSH PLATE SPECIAL FINISH OPTIONS AND CODES

› Satin Brushed Stainless Steel | **DC3090.1**

› Ceramic Coated Finish | **DC3090.6.xx**

› Powder Coated Finish | **DC3090.5.xx**