DOLPHIN



DC3150.1

WALL MOUNTED ULTRAFLUSH WC SET – ELECTRONIC

DETAILS

› **Full set with all items included for a working WC**

› **Declarations of performance and conformity**

› **Dual flush volumes of 6/3 litres as standard, adjustable to 4.5/3**

› **Special Finishes: Satin Brushed Stainless Steel, Ceramic Coating, PVD, PPC in all RAL colours**

› The UltraFlush system reduces noise while efficiently circulating water around the pan, ensuring perfect cleaning and a more comfortable user experience

› Electronic actuation flush

› Pan & cistern weight tested to 400KG

› WRAS approved inlet valve

› Compliant with DEFRA Interim agreement

› EN14055 Class two compliant

› Working pressure: 0.1 to 16 bar

› Height adjustable cistern & pan

› Must be installed above the height of the opened toilet seat and seat cover to avoid false activation issues

› Designed to be hardwired into 240v circuit - no battery option available

› Optional Bluetooth connection to Dolphin App or gateway device (to take you to Dolphin cloud or BMS) to provide setting possibilities, diagnosis and usage statistics

› Opening in the final wall finish should be cut to the size of the flush plate, not to the size of the cistern opening

› Designed to be hardwired into 240v circuit - no battery option available

› 34mm minimum wall build up required

SET INCLUDES

› DC2013 UltraFlush WC pan and seat

› DB5511.E Electronic cistern (with frame)

› DB5570.E Flush plate

FLUSH PLATE SPECIAL FINISH OPTIONS AND CODES

› Satin Brushed Stainless Steel | **DC3150.1**

› Ceramic Coated Finish | **DC3150.6.xx**

› Powder Coated Finish | **DC3150.5.xx**

› PVD Coated Finish | **DC3150.3.xx**